

ECOSYS MA4000x



Series Built to Perform _____

MONO Multifunction Printer | PRINT > COPY > SCAN > FAX* | Series: MA3500x, MA3500fx, MA3500wfx, MA4000x, MA4000fx & MA4000wifx*



Main Specifications							
Model		ECOSYS MA3500x	ECOSYS MA3500fx	ECOSYS MA3500wfx	ECOSYS MA4000x	ECOSYS MA4000fx	ECOSYS MA4000wifx
Main Function		Copy, Print, Scan, Fax (ECOSYS MA4000fx/MA4000wifx/MA3500fx/MA3500wfx only)					
Processing Method		Laser exposure dry electrostatic transcription					
CPU		ARM Cortex A53 single 1.0GHz					
Print Speed (A4) (Mono)		35 ppm			40 ppm		
Scanning Speed (A4) Simplex/ Duplex (Mono/Color)	300dpi	Simplex (Mono/Color): 40ipm/23ipm, Duplex(Mono/Color): 80ipm/46ipm					
	600dpi	Simplex (Mono/Color): 18ipm/7ipm, Duplex(Mono/Color): 36ipm/14ipm					
Memory		Standard 1GB (Max. 1GB)					Standard 2GB (Max. 2GB)
Warm Up Time		19 seconds					29 seconds
Paper Capacity	Standard	250 sheets (Cassette) + 100 sheets (MPT)					
	Maximum	850 sheets (Main Unit + 250 sheets PF-1100 x2 + MPT)					
Paper Size	Cassette	Min. A6R - Max. A4 (Legal)					
	Option	Min. A6R - Max. A4 (Legal)					
	MPT	Min. 70mm x 148mm - Max. A4 (Legal)					
Paper Weight	Cassette	60 - 163 g/m²					
	Option	60 - 163 g/m²					
	MPT	60 - 220 g/m²					
Duplex Printing		Paper size: A5R - A4/Legal; Paper weight: 60 - 163 g/m²					
Output Capacity		Max. 150 sheets face-down					
Control Panel		5 lines LCD (128(W) x 64(H) Dot display)					4.3 inch Color Touch LCD Panel
Document Processor		Standard (Max. 50 sheets ADF Type)			Standard (Max. 50 sheets DSDP Type)		
Dimension (W x D x H) (Main Unit)		417mm x 412mm x 437mm					
Weight (Main Unit)		Approx. 19.0kg *excluding the toner container					
Power Consumption (Standard configuration)	Copy/Print Mode	534.4 W			574.4 W		
	Stand-by Mode	10.8 W					11.8 W
	Energy Saver	0.4 W					
Noise (ISO7779/ ISO9296)	Copy/Print Mode	52dB(A); Quiet Mode: 48dB(A)					
	Stand-by Mode	29dB(A)					
		Copy Functions (Standard)					
Copy Size		Min. 100mm x 148mm - Max. A4 (Legal)					
Resolution		600 x 600 dpi					
First Copy Time		6.4 seconds or less					
Zoom Ratio (Manual)		25% - 400% (1% per Step)					
Multiple Copy		1 - 999					
		Print Functions (Standard)					
Resolution		300 x 300 dpi, 600 x 600 dpi, Fast1200, Fine1200					
PDL/Emulations		PCL6 (PCL5e, PCL-XL), KPDL3 (Postscript 3 compatible), PRESCRIBE, Line Printer, IBM Proprinter, Epson LQ-850, PDF Direct Print					
First Print Time		6.4 seconds or less					
Interface		USB 2.0 High Speedx1; Ethernet 10BASE-T/100BASE-TX/1,000BASE-T; USB Host Interface (USB Host)x1; 802.11b/g/n/ac/Wireless LAN/WiFi Direct (ECOSYS MA4000wifx only)					
Network Printing		TCP/IP, FTP, LPR, Port9100, NetBEUI, Apple Bonjour					
E-mail printing		Data printing of E-mail received data Data format : PDF, PS, Text, TIFF, JPEG, XPS, OpenXPS					
Secure printing		IPP over TLS					
Mobile Printing		AirPrint, Mopria, KYOCERA Mobile Print. KYOCERA MyPanel					
		Scan Functions (Standard)					
Send Size		Min. 50mm x 50mm - Max. A4 (Legal)					
Resolution		600dpi, 400dpi, 300dpi, 200dpi, 200x400dpi, 200x100dpi, 1200x1200dpi (Only TWAIN driver and WIA driver)					
File Format		TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPEG/High-compression PDF), PDF/A					
Image Type Mode		Text, Photo, Text + Photo, Light text + Fine line, Text (for OCR)					
Transmission Type		Scan to SMB; Scan to E-mail ; Scan to FTP or FTP over TLS; Scan to USB; TWAIN Scan; WSD Scan, WIA Scan					
Address Storage		300 addresses (Common address list), 50 groups (Group address list)					
		Fax Functions (ECOSYS MA4000fx/MA4000wifx/MA3500fx/MA3500wfx only)					
Original Size		Min. A6R - Max. A4 (Legal)					
Coding Method		MMR, MR, MH, JBIG					
Transmission Speed		33.6 kpbs					
Transmission Time		3 sec. or less					
Network FAX		Yes					
		Consumables & Options					
Toner Kit (Page Yield in accordance with ISO/ IEC 19752)		TK-1295 (3,000 pages)			TK-1275 (7,200 pages) TK-1285 (12,000 pages)		
Capacity of Start up Toner		1,000 pages			3,600 pages		
Maintenance Kit		MK-1295 (60,000 pages) (Except Taiwan, Korea, Philippines)			MK-1265 (70,000 pages) (Except Taiwan, Korea, Philippines)		
Paper Feeder		PF-1100: 250 sheets (Max. x2)					
Card Authentication		Card Authentication Kit(B)					



KYOCERA's Premium Business Partner

Mermaid 1 CHSL, Plot no. 32/33, Sector 11, CBD Belapur,
Navi Mumbai, Maharashtra-400614 | Tel : +91-22-66662040
Email : info@tirthoffice.com | Web : www.tirthoffice.com



Kyocera Document Solutions India Pvt. Ltd.

Block A, First India Place, Sushant Lok Phase-1,
M. G. Road, Gurugram-122002 (Haryana), India
Tel: +91-124-4671000 / Fax: +91-124-4671001

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ** Depending on the country